

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Product Evaluation Report

of

Euro-Wall, LLC
Euro-Pivot Inswing and Outswing Door
(HVHZ) (Impact)

for

Florida Product Approval

FL# FL22410

Report No. 7548

Current Florida Building Code

Method: 1 − D (Engineering Evaluation)

Category: Exterior Doors

Sub – Category: Swinging Exterior Door Assemblies

Product: Euro-Pivot Inswing and Outswing Door

(HVHZ) (Impact)

Material: Aluminum 6063-T5

Product Dimensions: See Installation Instructions, EWS018

Prepared for:

Euro-Wall, LLC P.O. Box 8007 North Port, FL 34290


Prepared by:

Hermes F. Norero, P.E.

Florida Professional Engineer # 73778 Date: 6/16/2023

Contents:

Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



FL#: FL17838 Date: 9/29/2023 Report No: 7548

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Manufacturer: Euro-Wall, LLC

Product Category: Exterior Doors

Product Sub-Category: Swinging Exterior Door Assemblies

Compliance Method: State Product Approval Method (1)(d)

Product Name: Euro-Pivot Inswing and Outswing Door System

(HVHZ)(Impact)

This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for Euro-Wall, LLC Scope:

based on Method 1d of the State of Florida Product Approval, Department of Business and

Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of

the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions EWS018, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

Limits of Use:

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, including the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and does not require an impact resistant covering.
- 4. Site conditions that deviate from the details of installation instructions EWS018 require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions **EWS018** for size and design pressure limitations.







FL#: FL17838Date: 9/29/2023
Report No: 7548

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Quality Assurance: The manufacturer has demonstrated compliance of manufacture of products in

accordance with the current Florida Building Code for manufacturing under a quality $% \left(1\right) =\left(1\right) \left(1$

assurance program audited by an approved quality assurance entity through **National Accreditation & Management Institute** (FBC Organization # QUA1789).

Performance Standards: The product described herein has been evaluated per:

• TAS 201-94

• TAS 202-94

TAS 203-94

Referenced Data:

1. Product Testing performed by Blackwater Technical Services Inc.,

(FBC Organization #: TST10394)

Report: Dated: BT-EUW-17-002 06/14/2017

Signed & Sealed: Constantin Bortes Florida P.E. No: 77915

BT-EUW-21-001 04/15/2021

Signed & Sealed: Michael D. Caldwell Florida P.E. No: 49979

2. Material Certification

Miami Dade County RER Notice Acceptance

Current NOA for SentryGlas Interlayer by Kuraray America, Inc.

3. Quality Assurance

National Accreditation & Management Institute

(FBC Organization #: QUA1789)

Installation:

Refer to Installation Instructions (**EWS018**) for anchor spacing and more details of the installation requirements.

Design Pressure:

Refer to Installation Instructions (**EWS018**) for design pressures based on size, configuration, and glass types.